

# ***OHSWEKEN SPEEDWAY'S***

## ***FLAGPOLE AND CHAIN RACE***

### ***2011 OFFICIAL RULES***

**Ohsweken Speedway reserves the right to alter or amend these rules at any time in the interests of safety, cost control or fair competition. The safety of each vehicle and all equipment is the complete responsibility of the driver/owner, and the driver/owner acknowledges this responsibility by participating in any activity at Ohsweken Speedway.**

**Must be over 16 years of age.**

**All vehicle participating are subject to technical inspection.**

**Any driver that is considered to be driving in an unsafe manner or intentionally hits a drivers door will be black flagged and not allowed to continue.**

**Any unsafe situations will be temporarily stopped with the red flag.**

### ***VEHICLE PERMITTED***

Any 2 or 4 wheel drive car or minivan. No fullsize vans , No SUVs, No Pick ups, No Jeeps.

### ***BODY***

Doors must be either welded, bolted,tied with seatbelts, chained or wired shut. Maximum 12"x 72" x 1/4" plate allowed on doors must be bolted with a minimum of 4 heavy bolts .

Hood must have a minimum 12" hole, hood can be wired, chained or bolted shut.

Bumpers can be from another vehicle but cannot be wider that original bumper (no sharp edges).No homemade bumpers.

All glass and flammable material must be removed with the exception of

-Stock type driver and passenger seat, headrest mandatory. Racing seat allowed. No fiberglass seats.

All taillights headlights, and trim must be removed.

### ***WINDSHIELD***

Removing the windshield is recommended. If windshield is removed it must be replaced with 1" heavy gauge mesh. A minimum of one 1" solid bar or minimum 1 1/4" x 0.095" tubing or 1 1/2" x 3/16" flat bar in the center of the windshield area.

### ***BATTERY***

Can remain in stock position. Can be moved and must be securely mounted to floor. Must be covered or in a spill proof container.

### ***FUEL TANK***

Original gas tank in original position under floor allowed. The gas tank can remain under the trunk floor if it is more than 20" from the rear bumper. Must have secure straps and no leaks.

Gas tank that is behind the rear wheels less than 20" from the rear bumper must be replaced with a steel fuel tank capacity of eight gallons or less or racing fuel cell. Must be placed between rear wheels. Must be securely mounted with a minimum of two straps 1" x 1/8" bolted to floor. Tank must be covered with air bag or metal.

Rubber fuel lines cannot run inside the interior.

No leaking fuel lines.

Steel fuel filters only (no plastic filters).

### ***FUEL INJECTION***

Can be changed to any carburetor.

### ***BRAKES***

Brakes must be working.

### ***FIREWALL***

Holes in front firewall must be patched with minimum 22 gauge steel.

### ***WHEELS AND TIRES***

Any wheels allowed. Any size street tire. Temporary spares allowed. Doubled tires allowed. Inner tubes allowed. No solid tires. No racing tires. No tire shaving, grooving or sipping. Hub caps and wheel weights must be removed.

### ***SUSPENSION***

Any springs, struts and shocks. No solid suspension. Weak or rusty parts can be reinforced or braced.

### ***COOLING SYSTEM***

No anti-freeze. Water only. Cooling system must be flushed with water.

Any rad allowed. Any electric fan allowed.

### ***ENGINE***

Engine swaps allowed.

Aftermarket performance filters and cone type filters allowed.

### ***TRANSMISSION***

Any transmission allowed. Any type shifter allowed.

### ***DIFFERENTIAL***

Locked rear ends allowed. Welding of the spider gears allowed. Limited slip allowed.

### ***CHAIN RACE***

Must be a minimum of 2' between vehicles.

### **Rear car**

Engine can not run.

Must have engine or transmission. Engine must have head, valve cover, oil pan and engine mounts everything else can be removed.

Removing the fuel tank and battery recommended.

Hood, trunklid or hatch can be removed.

Rad and bumpers can be removed.

### ***SAFETY***

An approved DOT full face helmet must be worn in all race events. Helmet must be in good condition. Snell SA2000 or better recommended. Eye protection must be worn if the helmet has no visor.

Stock seat belt allowed must be in good condition, 5 point racing belts recommended.

Long sleeves and long pants must be worn.

Drivers fire suit and gloves recommended. Treated long pants and treated long sleeve shirt recommended.

Flame retardant solution 6oz. Boric acid, 1 gallon water, 9oz. Borax. Soak in solution, do not rinse. Soak in solution after washing.

Window net recommended.

Door bars recommended.

### ***Rule Book Disclaimer***

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events and by participating in these events all participants are deemed to have complied with these rules. No expressed or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to participant, spectator or official. The tech director shall be empowered to permit minor deviations from any of the specifications herein or impose any further restrictions that in his/her opinion do not meet the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alterations or specifications. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

For track info go to [www.ohswekenspeedway.com](http://www.ohswekenspeedway.com)

Any questions regarding rules contact Glen Hils at 905 628-1716